

<b>2" FLEXNET</b>					
<b>5/8" TWD @ 92% EU, 0% SLOPE</b>					
TWD INLET Q (GPM)		1.46	1.84	2.13	2.50
TWD AVG. Q (GPM/100')		0.22	0.34	0.45	0.67
OUTLET SPACING	Hf	MAXIMUM MANIFOLD LENGTH			
30"	1 PSI	98'	85'	78'	70'
	2 PSI	128'	110'	98'	90'
36"	1 PSI	111'	96'	87'	78'
	2 PSI	141'	123'	111'	99'
40"	1 PSI	120'	103'	93'	83'
	2 PSI	150'	130'	120'	107'
60"	1 PSI	155'	130'	120'	110'
	2 PSI	195'	170'	155'	140'
72"	1 PSI	174'	150'	132'	120'
	2 PSI	222'	192'	174'	156'
80"	1 PSI	187'	160'	147'	127'
	2 PSI	240'	207'	187'	167'

<b>4" FLEXNET</b>					
<b>5/8" TWD @ 92% EU, 0% SLOPE</b>					
TWD INLET Q (GPM)		1.46	1.84	2.13	2.50
TWD AVG. Q (GPM/100')		0.22	0.34	0.45	0.67
OUTLET SPACING	Hf	MAXIMUM MANIFOLD LENGTH			
30"	1 PSI	325'	278'	253'	228'
	2 PSI	415'	355'	323'	290'
36"	1 PSI	363'	315'	282'	255'
	2 PSI	462'	399'	363'	327'
40"	1 PSI	390'	333'	303'	273'
	2 PSI	497'	427'	387'	350'
60"	1 PSI	510'	435'	400'	360'
	2 PSI	650'	555'	505'	455'
72"	1 PSI	570'	492'	450'	402'
	2 PSI	726'	624'	570'	510'
80"	1 PSI	607'	527'	480'	433'
	2 PSI	773'	673'	607'	547'

<b>3" FLEXNET</b>					
<b>5/8" TWD @ 92% EU, 0% SLOPE</b>					
TWD INLET Q (GPM)		1.46	1.84	2.13	2.50
TWD AVG. Q (GPM/100')		0.22	0.34	0.45	0.67
OUTLET SPACING	Hf	MAXIMUM MANIFOLD LENGTH			
30"	1 PSI	203'	175'	158'	143'
	2 PSI	260'	223'	203'	183'
36"	1 PSI	228'	195'	177'	162'
	2 PSI	291'	249'	228'	204'
40"	1 PSI	243'	210'	190'	173'
	2 PSI	313'	270'	243'	220'
60"	1 PSI	315'	275'	250'	225'
	2 PSI	405'	350'	315'	285'
72"	1 PSI	360'	306'	276'	252'
	2 PSI	456'	390'	354'	324'
80"	1 PSI	380'	327'	300'	267'
	2 PSI	487'	420'	380'	347'

<b>6" FLEXNET</b>					
<b>5/8" TWD @ 92% EU, 0% SLOPE</b>					
TWD INLET Q (GPM)		1.46	1.84	2.13	2.50
TWD AVG. Q (GPM/100')		0.22	0.34	0.45	0.67
OUTLET SPACING	Hf	MAXIMUM MANIFOLD LENGTH			
30"	1 PSI	725'	620'	558'	505'
	2 PSI	915'	788'	710'	643'
36"	1 PSI	810'	690'	630'	570'
	2 PSI	1,029'	879'	801'	726'
40"	1 PSI	867'	750'	683'	617'
	2 PSI	1,103'	950'	860'	780'
60"	1 PSI	1,125'	975'	890'	800'
	2 PSI	1,430'	1,225'	1,125'	1,015'
72"	1 PSI	1,260'	1,080'	990'	900'
	2 PSI	1,620'	1,380'	1,260'	1,140'
80"	1 PSI	1,367'	1,167'	1,067'	967'
	2 PSI	1,733'	1,487'	1,347'	1,220'

<b>8" FLEXNET</b>					
<b>5/8" TWD @ 92% EU, 0% SLOPE</b>					
TWD INLET Q (GPM)		1.46	1.84	2.13	2.50
TWD AVG. Q (GPM/100')		0.22	0.34	0.45	0.67
OUTLET SPACING	Hf	MAXIMUM MANIFOLD LENGTH			
30"	1 PSI	1,100'	950'	863'	775'
	2 PSI	1,398'	1,200'	1,093'	988'
36"	1 PSI	1,230'	1,065'	975'	879'
	2 PSI	1,575'	1,350'	1,230'	1,110'
40"	1 PSI	1,333'	1,150'	1,033'	933'
	2 PSI	1,693'	1,450'	1,317'	1,187'
60"	1 PSI	1,725'	1,475'	1,350'	1,225'
	2 PSI	2,200'	1,885'	1,715'	1,550'
72"	1 PSI	1,950'	1,680'	1,530'	1,380'
	2 PSI	2,460'	2,130'	1,938'	1,740'
80"	1 PSI	2,067'	1,800'	1,633'	1,467'
	2 PSI	2,633'	2,267'	2,067'	1,867'

TWD = Thinwall Dripline  
 EU = Emission Uniformity