

PC DRIPPERLINE w/ CHECK VALVE

- Pressure compensating between 7.5 and 50 psi.
- Check valve opens at low pressure of 7.5 psi.
- Includes check valve to prevent drainage of line on shut down.
- Anti-syphon feature to prevent dirt from being sucked back if a vacuum occurs.
- Consistent clog free performance.
- 2 flow rates available.
- Wide variety of spacings available.
- Long lasting silicone diaphragm.

DISCHARGE RATES (GPH)

Dripperline Flow Rate	10 psi	20 psi	30 psi	40 psi	50 psi
0.6 gph	0.63 gph	0.64 gph	0.64 gph	0.65 gph	0.64 gph
1.0 gph	0.99 gph	1.00 gph	1.01 gph	1.02 gph	1.03 gph

MAX LENGTH OF RUN (FEET)

Dripperline Dimensions	Starting Line Pressure	0.6 gph			1.0 gph		
		12" Spacing	18" Spacing	24" Spacing	12" Spacing	18" Spacing	24" Spacing
0.560" ID x 0.660" OD (17 mm Brown)	20 psi	265'	400'	490'	200'	260'	350'
	30 psi	337'	475'	595'	240'	340'	425'
	40 psi	410'	550'	700'	280'	420'	500'
0.600" ID x 0.700" OD (18 mm Black)	20 psi	330'	440'	570'	240'	320'	400'
	30 psi	410'	555'	685'	285'	395'	480'
	40 psi	490'	670'	800'	330'	470'	560'