

# BLU-LOCK® x DRIP-LOCK®

For ½" Micro Irrigation Pipe

### Blu-Lock® Features

- Low insertion force makes installation fast
- Works with all HDPE pipe ASTM D2239 listed SIDR 15 100 psi and SIDR 19 80 psi pipe
- Fittings are releasable and reusable with the Blu-Lock® release tool
- Patented design is 100% tool and chemical free
- Blu-Lock® technology will ensure lower friction loss for better water efficiency
- Built tough fittings made from UV-resistant ABS, stainless steel and EPDM seals are designed and tested to ensure toughness
- For use on the downstream side of the station valves, not rated for mainline use

### Specifications

Blu-Lock® ¾" (1.9 cm) Lateral Pipe Fittings:

- Working pressure: 10-100 psi (0.69-6.9 bar)

Blu-Lock® 1" (2.5 cm) Lateral Pipe Fittings:

- Working pressure: 10-100 psi (0.69-6.9 bar)

### Drip-Lock® Features

- Fittings are releasable and reusable with the Drip-Lock® release collar
- Patented design requires no glue or tools for installation
- Low insertion force makes installation quick and easy
- ½" Drip-Lock® works with tubing from 16 mm to 18mm
- Drip-Lock® technology ensures lower friction loss for better water efficiency
- Built tough fittings made from UV-resistant
- ABS, stainless steel and EPDM seals

### Specifications

- Compatibility range: 16mm (about .630") to .710" (about 17.8 mm) outside diameter
- Burst pressure exceeds 100 psi (6.9 bar)
- Operating pressure: 0-50 psi (0-3.4 bar)



BL-401-101-DL



BL-402-101-DL

## TEES

	Part Number	Nom. Size	Description	SKU
Push x Push x Push	BL-401-101-DL	1"	1" x 1" x ½"	37360
	BL-402-101-DL	¾"	¾" x ¾" x ½"	37361