

## SRM

The SRM is an economical short-range rotor that offers a convenient and efficient alternative to spray heads.

### Key Benefits

- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Through-the-top arc adjustment for easy installation
- Standard factory-installed 2.0 nozzle speeds installation
- QuickCheck™ arc mechanism for fast arc adjustment

### Operating Specifications

- Nozzle choices: 8
- Flow: 0.42 to 4.3 GPM
- Operating pressure range: 20 to 100 PSI
- Nozzle trajectory: 14° approximately
- Radius: 15' to 34'
- Recommended pressure range: 30 to 50 PSI
- Precipitation rate: 0.6 in/hr approximately
- Warranty period: 1 year

### User-Installed Options

- Drain check valve (up to 7' of elevation) (P/N 462078SP)

Radius: 15' to 34'  
Flow: 0.42 to 3.4 GPM  
Inlet Size: ½"



#### SRM-04

Pop-up Height: 4"  
Overall Height: 6-5/8"  
Exposed Diameter: 1-1/8"  
Inlet Size: ½" NPT

---

Model	Description
SRM-04	4" Pop-up, adjustable arc, 8 standard nozzles

---

## SRM NOZZLE PERFORMANCE DATA

Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
.50 ● Dk. Green	30	14	0.42	0.41	0.48
	40	15	0.5	0.43	0.49
	50	16	0.58	0.44	0.5
.75 ● Dk. Green	30	15	0.64	0.55	0.63
	<b>40</b>	<b>16</b>	<b>0.75</b>	<b>0.56</b>	<b>0.65</b>
	50	17	0.85	0.57	0.65
1.0 ● Dk. Green	30	18	0.85	0.51	0.58
	40	19	1	0.51	0.59
	50	19	1.1	0.57	0.66
1.5 ● Dk. Green	30	21	1.3	0.57	0.66
	<b>40</b>	<b>22</b>	<b>1.5</b>	<b>0.6</b>	<b>0.69</b>
	50	22	1.7	0.67	0.77
2.0 ● Dk. Green	30	24	1.7	0.55	0.64
	40	25	2	0.62	0.71
	50	25	2.3	0.71	0.82
2.5 ● Dk. Green	30	27	2.2	0.58	0.67
	<b>40</b>	<b>28</b>	<b>2.5</b>	<b>0.6</b>	<b>0.69</b>
	50	28	2.8	0.68	0.79
3.0 ● Dk. Green	30	30	2.5	0.53	0.62
	40	31	3	0.6	0.69
	50	31	3.4	0.68	0.79
4.0 ● Dk. Green	30	33	3.7	0.65	0.76
	<b>40</b>	<b>33</b>	<b>4</b>	<b>0.71</b>	<b>0.82</b>
	50	34	4.3	0.72	0.83