

MixRite 566AG



Important Component Materials

Engine Assembly is Nylon 12
Body is Nylon 12 reinforced with fiberglass
Viton Extreme chemical piston seal
EPDM o-rings in Engine assembly
302 springs in engine assembly

Chemical check valve components

EPDM seal
Hastelloy spring
EPDM o-ring



- Ideal for hundreds of cleaning chemicals & fertilizers
- Suitable for sanitizers that are not corrosive when diluted to 1:100 (1%) or mild acids that do not create heat
- Accurately injects Vitamins and Minerals for Swine and Cattle production
- Minimum Flow rate is .088 GPM or 22oz per minute
- Maximum flow is 11 gpm
- Maximum operating pressure is 120 PSI
- Maximum Injection is achieved at less than 60 PSI



World Headquarters: DEMA Engineering Company
10020 Big Bend Blvd. • St. Louis, MO 63122 U.S.A. Tel: 1-800-325-3362 • Fax: 314-965-8319
Web site: www.demaeng.com • E-mail: sales@demaeng.com

DEMA[®]

We Dispense
SOLUTIONS

SYDNEY, AUSTRALIA • ZEEWOLDE, THE NETHERLANDS • SHANGHAI, CHINA • SÃO PAULO, BRAZIL