

2002 AquaSmart



2002 AquaSmart Performance

Nozzle Color	Nominal Flow (gph)	Nozzle Diameter (inches)	Swivels - Wetted Diameter (feet)									
			Orange	Black		Blue		Green	Red			
			Short Range	Medium Range w/ Deflector	Medium Range	Long Range w/ Deflector	Long Range	Inverted	Extra Long Range w/ Deflector	Extra Long Range		
Violet	5.3	0.033	9.8	4.9	11.5							
Gray	7.4	0.039	9.8	6.6	13.0	4.9	14.7	16.4				
Brown	9.3	0.043	11.5	8.2	13.0	6.6	16.4	16.4				
Blue	12.4	0.049	11.5	8.2	14.7	6.6	18.0	16.4				
Green	14.5	0.052	11.5	8.2	14.7	6.6	19.7	16.4				
Orange	18.5	0.058		8.2	16.4	8.2	23.0	16.4				
Yellow	25.1	0.069		9.8	18.0	9.8	24.6	16.4				
Red XL	9.3	0.037							3.3	23.0		
Black XL	10.5	0.039							4.9	23.0		
Ivory XL	12.4	0.043							6.6	23.0		

*Upside Down w/ Spring - 24" above ground level
Flow rate and wetted diameter (feet) at 29 psi. Tested at 10" above ground

Flow vs. Pressure

Nozzle Color	Nominal Flow (gph)	Pressure (psi)								
		20	25	30	35	40	45	50	55	60
Violet	5.3	5.2	5.2	5.3	5.4	5.5	5.5	5.6	5.5	5.5
Gray	7.4	7.4	7.4	7.4	7.4	7.5	7.5	7.5	7.5	7.4
Brown	9.3	9.1	9.3	9.2	9.1	9.1	9.1	9.1	9.1	9.1
Blue	12.4	12.5	12.2	12.4	12.4	12.3	12.3	12.3	12.2	12.2
Green	14.5	14.7	14.5	14.5	14.6	14.8	15.0	15.1	15.1	15.0
Orange	18.5	19.1	18.9	18.4	18.5	18.6	18.7	18.7	18.6	18.5
Yellow	25.1	25.3	25.0	25.0	25.0	25.1	25.3	25.1	25.0	25.0
Red XL	9.3		8.6	9.0	8.8	8.8	8.7	8.8	8.9	8.9
Black XL	10.5		10.1	10.7	9.9	9.9	10.0	10.4	10.5	10.7
Ivory XL	12.4		12.2	12.4	12.0	12.3	12.6	13.0	13.0	13.1

