



- ① FINISH GRADE OR TOP OF MULCH
- ② PLANT MATERIAL (SHRUB OR GROUND COVER)
- ③ CLEAN SOIL, AMENDED/NATIVE – FREE OF ROCK AND DEBRIS
- ④ SHRUBBLER THREAD 1/2” (SEE LEGEND FOR TYPE).
- ⑤ OPTION – (SEPERATE) ADAPTER 1/2” FNPT x 10–32 THREAD #41015, (SEPERATE) SHRUBBLER THREAD 10–32 UNF (360 – #31415 OR 180 – #31215).
- ⑥ LATERAL LINE PIPE, SEE PLAN FOR SIZE AND TYPE.
- ⑦ TEE/ELBOW, PVC SCH40, SIZE AS REQUIRED, SEE PLAN.
- ⑧ PVC SCH 80 RISER, THREADS BOTH ENDS, LENGTH AS NEEDED.

NOTE:
 SET ZONE PRESSURE TO 30 PSI.
 ADJUST SHRUBBLER RADIUS AS NEEDED.

NOTE:
 ANTELCO SHRUBBLER THREAD 1/2” SPECIFICATIONS:

ARC	MOD#	RADIUS	GPH @ PSI
360° CIR	31425	1.5–FT	13.0 @ 30
180° CIR	31225	2.0–FT	13.0 @ 30

00

ANTELCO SHRUBBLER® 360° OR 180° ON PVC RISER

N.T.S.

DETAIL–FILE