

1370

Adjustable Beta head with ½" (1,27 cm) bearing

1973

Whiz Head rotary sprinkler

1370



1973



ENGLISH

WHIZ HEAD®	Pressure age (psi)	Flow (gpm)	Cover-Dia. (ft)
	30	3.4	40
	40	3.9	40
	50	4.4	40

METRIC

WHIZ HEAD®	Pressure age (bar)	Flow (l/min)	Cover-Dia. (m)
	2	12,8	12,2
	2,7	14,7	12,2
	3,5	16,6	12,2

FEATURES

1370

Beta impact spray heads provide outstanding performance at an affordable price. Made with high impact plastic, they are durable, keeping maintenance to a minimum.

- Includes five easily interchangeable, seven nozzles and 2 low-angle nozzles.
- No tool is required to change nozzles.
- ½" (1,27 cm) male threads
- Non-clog nozzle and straight-through flow design
- Sealed bearing keeps dirt and debris out
- Anti-backsplash arm keeps water off buildings
- Adjust pattern and spray with diffuser pin and exclusive Click-Set® trip collars
- Use 1370's for riser installations
- Diffuser pin maintains set spray pattern adjustment

1973

- Ideal for riser installations in planting areas
- ½" (1,27 cm) female threaded inlet
- Made of high-impact corrosion resistant plastic
- Stainless steel bearing and large orifice nozzle

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

18 Goodyear • Suite 110
Irvine • California • 92618
Tel: 949.580.3640
Fax: 949.580.3645

USA Toll Free: 866.4SIGNATURE

MANUFACTURING FACILITY

8800 N.Allen Rd.,
Peoria • Illinois • 61615
Tel: 949.580.3640
Fax: 949.580.3645

EUROPE & MIDDLE EAST

5 rue de la Vallee Yart
78640 Saint Germain de la Grange
France
Tel: +33.13.489.9056
Fax: +33.13.489.6025

REGIONAL OFFICES ASIA

NanXian Plaza • MinZhi Street • Shenzhen,
Guangdong Province • 518131
Tel: (86) 136.00419465 • Fax: (86) 755.83275012
SOUTH AMERICA
Av Paseo Los Bravos 6000 • Lo Barnechea
Santiago • Chile
Tel/Fax: +56 229.556220

www.SignatureControlSystems.com

MEXICO, CENTRAL AMERICA

Ribera Escondida 118 • Riberas Del Campestre
38080 Celaya • Gto. • Mexico
Tel/Fax: +52 (461) 614.2322

AFRICA

P.O. Box 1260 • Strubensvalley 1735
Roodepoort • South Africa
Office & Mobile: +27 82 553 9093 • Fax: 086 670 6318