

SPRAYS - RESIDENTIAL

STANDARD

63S-03

3" (7,6 cm) Pop-Up Body

63S-04

4" (10,2 cm) Pop-Up Body

including MAN Nozzle

2½" (6,3 cm) Pop-up

Factory Installed MAN Nozzle

63S-0312

63S-0315

63S-0317

4" (10,2 cm) Pop-up

Factory Installed MAN Nozzle

63S-0412

63S-0415

63S-0417

63S-03



63S-04



SPECIFICATIONS

OPERATING RANGE:

15-60 psi (1-4,1 bar)

OPTIMUM PRESSURE:

30 psi (2 bar)

MAXIMUM PRESSURE:

60 psi (4,1 bar)

SEALING PRESSURE:

Less than 15 psi (1 bar)

POP-UP HEIGHT:

3" (7,6 cm) (63S-03)

4" (10,2 cm) (63S-04)

BODY HEIGHT:

5½" (13,0 cm) (63S-03)

6" (15,2 cm) (63S-04)

FLUSH RATE:

0.2 gpm (0,75 l/min)

INLET SIZE:

½" (12,7 mm) NPT Female thread

SCREEN MESH:

.045 sq. in. (1,14 mm²) / 1150 micron

PER BOX:

50 (63S-03 Series, 63S-04 Series)

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

18 Goodyear • Suite 110
Irvine • California • 92618
Tel: 949.580.3640
Fax: 949.580.3645

USA Toll Free: 866.4SIGNATURE

MANUFACTURING FACILITY

8800 N.Allen Rd.,
Peoria • Illinois • 61615
Tel: 949.580.3640
Fax: 949.580.3645

EUROPE & MIDDLE EAST

5 rue de la Vallee Yart
78640 Saint Germain de la Grange
France
Tel: +33.13.489.9056
Fax: +33.13.489.6025

REGIONAL OFFICES

ASIA
NanXian Plaza • MinZhi Street • Shenzhen,
Guangdong Province • 518131
Tel: (86) 136.00419465 • Fax: (86) 755.83275012

SOUTH AMERICA
Av Paseo Los Bravos 6000 • Lo Barnechea
Santiago • Chile
Tel/Fax: +56 229.556220

www.SignatureControlSystems.com

MEXICO, CENTRAL AMERICA

Ribera Escondida 118 • Riberas Del Campestre
38080 Celaya • Gto. • Mexico
Tel/Fax: +52 (461) 614.2322

AFRICA

P.O. Box 1260 • Strubensvalley 1735
Roodepoort • South Africa
Office & Mobile: +27 82 553 9093 • Fax: 086 670 6318