

T-SPRAY DESIGN CRITERIA

	PSI					
	15	20	25	30	35	40
#6 T-Stem - Gold						
Flow (gpm)	0.98	1.14	1.27	1.40	1.52	1.63
Diameter at 1.5 ft ht (ft)	15.5	17.0	18.0	19.0	20.0	21.0
Diameter at 3.0 ft ht (ft)	17.5	18.5	19.5	20.5	21.5	22.0
#7 T-Stem - Lime						
Flow (gpm)	1.34	1.56	1.73	1.90	2.05	2.20
Diameter at 1.5 ft ht (ft)	17.0	18.5	19.5	20.5	21.0	21.5
Diameter at 3.0 ft ht (ft)	18.5	19.5	20.5	21.5	22.5	23.0
#8 T-Stem - Lavender						
Flow (gpm)	1.73	2.01	2.23	2.45	2.65	2.85
Diameter at 1.5 ft ht (ft)	18.0	19.5	20.5	21.0	21.5	22.0
Diameter at 3.0 ft ht (ft)	19.0	20.0	21.0	22.0	23.0	23.5
#8 T-Stem HA - Dark Purple						
Flow (gpm)	1.73	2.01	2.23	2.45	2.65	2.85
Diameter at 1.5 ft ht (ft)	25.5	27.5	29.0	30.0	31.0	32.0

Sprinkler performance may vary with actual field conditions. Minimum recommended riser height is 1.5 ft.